Connector FH12-10S-0.5SH(55)

As a professional high quality E-Comp Connector FH12-10S-0.5SH(55)manufacture, you can rest assured to buy E-Comp Connector FH12-10S-0.5SH(55) from our factory and we will offer you the best after-sale service and timely delivery. We will seek to continuously improve our products, processes, and the effectiveness of our quality management system to better serve our customers.

Product Description

The following is the introduction of high quality E-Comp **Connector FH12-10S-0.5SH(55)**, hoping to help you better understand E-Comp **Connector FH12-10S-0.5SH(55)**. Welcome new and old customers to continue to cooperate with us to create a better future! We strive to meet customer needs, delivery requirements and we maintain top quality standards and a highly skilled work force. We are dedicated to providing our customers with the highest quality products manufactured to strict quality standards that meet or exceed our customers' requirements.

E-Comp Group FH12-10S-0.5SH(55) Integrated Circuit Parameter (Specification)	
Digi-Key Part Number	HFJ110TR-ND - Tape & Reel (TR) HFJ110CT-ND - Cut Tape (CT) HFJ110DKR-ND - Digi-Reel®
Manufacturer	Hirose Electric Co Ltd
Manufacturer Product Number	FH12-10S-0.5SH(55)
Description	CONN FFC BOTTOM 10POS 0.50MM R/A
Manufacturer Standard Lead Time	28 Weeks
Detailed Description	10 Position FFC, FPC Connector Contacts, Bottom 0.020" (0.50mm) Surface Mount, Right Angle

E-Comp Group FH12-10S-0.5SH(55) Integrated Circuit Feature And Application	
TYPE	DESCRIPTION
Category	Connectors, Interconnects FFC, FPC (Flat Flexible) Connectors FFC, FPC (Flat Flexible) Connector Assemblies
Mfr	Hirose Electric Co Ltd

Series	FH12
Package	Tape & Reel (TR) Cut Tape (CT) Digi-Reel®
Product Status	Active
Flat Flex Type	FFC, FPC
Mounting Type	Surface Mount, Right Angle
Connector/Contact Type	Contacts, Bottom
Number of Positions	10
Pitch	0.020" (0.50mm)
Termination	Solder
FFC, FCB Thickness	0.30mm
Height Above Board	0.079" (2.00mm)
Locking Feature	Flip Lock
Cable End Type	Straight
Contact Material	Phosphor Bronze
Contact Finish	Gold
Housing Material	Polyamide (PA), Nylon
Actuator Material	Polyphenylene Sulfide (PPS)
Features	Zero Insertion Force (ZIF)
Voltage Rating	50V
Operating Temperature	-40°C ~ 85°C
Material Flammability Rating	UL94 V-0
Current Rating (Amps)	0.5A
Contact Finish Thickness	-
Housing Color	Beige
Actuator Color	Brown
Mating Cycles	20
Base Product Number	FH12

If you want to know more about FH12-10S-0.5SH(55) connector, or other related resistors, diodes/transistors, inductors.... and other products FH12-10S-0.5SH(55) connectors, you can contact us.

Phone: +86-13802700694 **E-mail:** martin@usecgi.com