



Electric Cargo Van

Hilima Company is a professional manufacturer of large-scale Electric Cargo Van and new energy vehicles. Its products are well-known at home and abroad for their durability and excellent performance. Most of the products have been approved by the European Union and the United States.

11. Product introduction of the Electric Cargo Van

Electric Cargo Van

- ·Simple and tough appearance, with many technological elements, makes the car appear both fashionable and elegant
- ·Its nose is narrow, wheelbase is short, turning radius is small, can easily pass the narrow complex space
- ·It has a huge trunk with a huge capacity of 3.3 cubic meters and is your mobile small warehouse
- ·Electric Cargo Van has been certified by the EEC of the European Union and DOT of the United States.

2. Product parameter of the Electric Cargo Van

project	Standard Edition	Plus version
---------	------------------	--------------

Shandong Heima Construction Machinery Co. LTD





		I			iciiiiiacii.com
	Body structure type	Separate fra		Separate fra	
	Overall size (mm)	3490*1490*	1685	3490*1490*	1685
	Front / rear track width (mm)	1250/1250		1250/1250	
Basic parameters of vehicle	Wheelbase (mm)	2350		2350	
	Front/rear overhang (mm)	480/660		480/660	
	Approach / departure angle (°)	31/25		31/25	
or verlide	Minimum ground clearance (mm)	>140		>140	
	Minimum turning diameter (m)	<9	<9		
	Curb weight (kg)	845	854	960	969
	Rated loading mass (kg)	540 466		425	351
	Seating capacity persons	Single seat	Double seat	Single seat	Double seat



Maximum total mass (kg)	1450		total mass 1450		1450	
Fron/ rear axle load (kg)	519/931 555/895		554/896	590/860		
Door opening type	The front left and right doors are opened in a forward direction, the rear right door is opened on the rear side , and the tailgate is opened on the left side					
Container volume (m³)	About 2.6 CBM (Available volume of CO driver's seat included)		3.3 About 3.3			

3. Product feature and application of the Electric Cargo Van











3.3 cubic meters of super-large volume space

The safety of drivers and passengers is guaranteed





Large capacity battery pack, the range is more guaranteed

Detailed parameters

	Battery type	Lithium Iron Phosphate	Lithium Iron Phosphate	
Power	Fixing method of power battery	Tiled and fixed between longitudinal beams		
battery	Rated total voltage (V)	76.8	76.8	
	Total battery capacity (kwh)	10.37 (20.74 rear mounted)	20.74	

Shandong Heima Construction Machinery Co. LTD



E-mail: zlh7611@hotmail.com

					VV VV VV.110	ellimacn.com
	BMS battery system	management	•		•	
	Charging type	charging power.		1.8kw, 5h)	/ (3.3kv 8h)	N,
	Endurance r	mileage (km)		orking ndition ≥120	Working	g n ≥ 240
	Motor type			Permanent synchronou	_	
	Protection	level		IP67	IP67	
	Insulation	class		Н	Н	
	Rated / pe	ak power (kW)		7.5/15 7.5/15		
	Maximum (N·m)	torque of motor		90	90	
Drive motor	Driving typ	е		Rear direct	drive (rear	
	Max speed	l(km / h)		71	71	
	Max climbi	ng degree (%)		≥20	≥20	
	Warranty (motor, electric contr ery)	ol,	5 years or 2	200000 km	
	Rear axle	final drive ratio		Single stag speed ratio		
	Shift mode			Electronic r	•	
controller	Vehicle co	ntrol unit				The vehicle
CONTROLLER	Motor cont	roller		•	•	control

Shandong Heima Construction Machinery Co. LTD

77/\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	V			www.ne	www.heilimacn.com		
	Body contro	ol module			function is integrat ed in the motor controlle r		
	suspensi	Front suspension	McPherson independer suspension	nt			
	system	Rear suspension	Leaf spring	Leaf spring			
	brake	front brake	Disc hydraulic brake	Disc hydraulic brake			
		Rear brake	Drum hydraulic brake	Drum hydraulic brake			
Chassis configurati	rigging	Brake pedal assist category	Electric vacuum assist	Electric vacuum assist			
		Parking brake	mechanic al	mechanic al			
Steer		Steering gear	Rack and pinion type	Rack and pinion type			
	Steering gear	Steering column	Energy feedback type	Energy feedback type			
		Power steering type					
	wheel	Tire size	165/70R1 3	165/70R1 3			

Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101

E-mail: zlh7611@hotmail.com



						W W W	IIIIIIacii.com
		Rim			Steel	Steel	Black steel wheel
		Rim trim cov	ver		0	0	
		Spare tire (f	ull siz	e)			
	ABS+EBD				•	•	
	Electronic	Stability Progra	am				
	Door open	alarm			•	•	
	Safety belt	reminder			•	•	
Security configurati on	Manual an	ti glare interior	rear				
	Rear rever	Rear reversing radar					
	Pedestrian	Pedestrian reminder			•	•	low speed alarm
	Front / rea	r bumper	bumper		•/•	•/•	
	Side door	anti collision be	eam		•	•	
			Far and low bea		halogen	halogen	
		on lamp	From pos		LED	LED	
Security configur ation	configur p	urn signal (low part of front pumper)	er/	LE	D	LED	

Shandong Heima Construction Machinery Co. LTD



A *		NE <u>RY</u>
	LIGIM	A
HA		

				www.neiiin	14011.00111
	Front fog	lamp			
	Daytime re				
		Revers ing lamp	LED	LED	right
	Rear	Rear turn signal	LED	LED	
	combin ation lamp	Positio n light	LED	LED	
		Brake light	LED	LED	
		Rear fog lamp	LED	LED	left
	Rear ceiling lamp		LED	LED	
	Reading lamp		LED	LED	
	Folding the remote key		•	•	
Car anti	Spare key (straight handle machine)		•	•	
theft	Central loc (central co module)		•	•	
	Automatic lock	speed			



							ww.neiiimach.com
		Car anti th	neft	Mechanical anti theft		Mecha anti the	
		Driver's ai	rbag				
	Passive	Co driver's	s air bag				
	safety	Driver / Co three-poin seat belt		/—	•/•	/—	•/•
	Wiper unit			Single	arm	Single	arm
	Exterior	Lens adju		Manua manua		Manua manua	
	rearview mirror	With side turn signal (LED)		•		•	
	Information Board			•		•	
	Hardtop	Hardtop			•		
Interior	Van Soft to	op device / opening				0/man	ual
exterior decorati on	Steering wheel	Triplicat e		•		•	
device		front seat	Driver' s seat	Man ual	Man ual	Man ual	Man ual
	chair	adjustm ent mode	Passe nger seat	_	Man ual	_	Man ual
	Operation regulator	mode of wir	ndow	Electric		Electri	С
	12V power	supply		1	1		
	USB interf	ace		3		3	

Shandong Heima Construction Machinery Co. LTD



E-mail: zlh7611@hotmail.com

						***************************************	iacii.com
	Auxiliary i	nstrument panel	•		•		
	Auxiliary instrument panel cup holder B-pillar lower guard		•		•		
			•		•		Shelt er belt retrac tor
	Roof inne	r armrest (right)					
	Sun	Main driver's seat	•	•	•	•	
	visor	Co driver's seat	_	•	_	•	
	Electric air co	onditioner			•		
	Air heater			•			
	Air conditioni	ng regulation mode		Electric	Electr	ic	
	External air c	irculation					
	Air circulation	in the vehicle		•	•		
	External ante	nna		•	•		
	Vehicle-mour	nted mobile Internet					
	Remote unlo	cking function					
	Remote quer	y of vehicle status					
Other	her Remote search function						
	Remote intell function	igent self-test diagnost	ic				
	Cruise contro	ol					

Shandong Heima Construction Machinery Co. LTD



E-mail: zlh7611@hotmail.com

				*******	neiiimach.d
ETC vehicle-Mo	ounted device		0	0	
	combination instrument	LCD touch screen	•	•	
Limit makel	Radio		•	•	
Liquid crystal combination instrument device	Bluetooth fund (music, phone		•	•	
device	Mobile Interne	et	•	•	
	Audio playbad	Audio playback		•	
	Astern video i	mage	•	•	
The speaker			2	2	
Reversing came	era		•	•	
Mobile intelliger mode)	Mobile intelligent audio (rear mounted mode)				Rear mounted mode, removab
Remote monitoring			•	•	
ECO operation mode		•	•		
One click Start	One click Start				
Braking energy recovery			•	•	

 $\hbox{``\bullet"} Standard\ configuration; \hbox{``\circ"} Optional; \hbox{``----}" There\ is\ no\ such\ configuration.$



E-mail: zlh7611@hotmail.com



