



Electric Moke

Hilima Company is a leading China Electric Moke manufacturer, supplier and exporter. Adhering to the pursuit of perfect quality of products, so that our Electric Moke have been satisfied by many customers. Customers in a variety of industries choose XX products for two simple reasons: the products are designed and manufactured to high quality standards, and they are available at a fair market value.

1. Product introduction of the ELECTRIC MOKE

ELECTRIC MOKE is the first product of our company, which follows the century-old classic and is the perfect return of a century-old classic model.

- All chassis and body are aluminum manganese alloy lightweight design.
- ELECTRIC MOKE has been certified by the EEC of the European Union and DOT of the United States
- E-MOKE has high - low automatic switch of the two - speed transmission, so that the car climbing is more powerful, high-speed is more stable.
- E-MOKE uses electronic self - brake system, which is safer and more efficient.
- MAX 20 KW AC motor, strong power, high efficiency.

2. Product parameter of the ELECTRIC MOKE

Measurement Parameter

Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101

E-mail: zlh7611@hotmail.com

(L*W*H)	3290*1530*1500 mm
Wheelbase	2120 mm
Wheel track front/rear	1280mm/1280mm
Ground Clearance	180mm
Max climbing ability	23°
Curb Weight	430Kg
Full load	960Kg
Range	160Kms
Seats	4

3. Product feature and application of the ELECTRIC MOKE



Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101

E-mail: zlh7611@hotmail.com

In the seaside, in the grassland, in the beautiful scenic spots, there are her beautiful figure.



A wonderful car for festive revelry



We are in the same club

Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101

E-mail: zlh7611@hotmail.com



Sea and sky, I am the most beautiful guy

Detailed parameters

Performance specs	Endurance mileage	km	92 kms/90km/h
		km	150kms/50km/h
	Max grade ability	%	40% (@15km/h)
Motor specs	Motor model		GLMI10A1
	Motor power (rated/peak)	KW	15kw/30KW
	Motor rpm (rated/max)	r/min	3500/7000
	Motor rated voltage	V	108 V
	Insulation class		H
	Protection class		IP65

Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101

E-mail: zlh7611@hotmail.com

	Motor controller		GLCI6008A2
Battery pack specs	Battery rated capacity	AH	166
	Battery pack rated voltage	V	108V
	Total energy	KWH	16
	Max continuous charge current	A	120
	Max continuous discharge current	A	145.6
	Peak discharge current	A	250 (Protected to 250 A)
	Standard voltage	V	103.6
	MAX voltage	V	116
	Battery pack weight	kg	131.2
	Battery cell model		18650
	Battery core type		Ternary lithium battery
	Battery working temperature	°	-20°-----60 °
	Battery pack cooling method		Natural cooling
	Excess voltage protection	V	4.15
	Under voltage protection	V	2.8
	System self-discharge rate		Keep 95% at 25 days, 25°C
IP rated		IP67	
Charger specs	Input voltage	V	220V±15 %
	Input current:	A	≤16A

	Efficiency :		≥93%
	Power factor :		≥0.98
	Rated output voltage :	V	60V DC
	Cooling method		Forced air cooling
	Charging time 20A/3.3KW	hours	3-6 hours from 20%----100%
DC SPECS	Input voltage range	V HZ	AC90----264V 50HZ
	Input rated current	A	50----198
	Output voltage	V	14
	Rated current	A	72
	Peak current	A	100
	Rated power	KW	1
	Peak power	KW	1.2 (6 mins)



Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101

E-mail: zlh7611@hotmail.com