



Gasoline Moke

Hilima Company is a professional manufacturer of large-scale Gasoline Moke. Its products are well-known at home and abroad for their durability and excellent performance. You can rest assured to buy Gasoline Moke from our factory and we will offer you the best after-sale service and timely delivery.

1. Product introduction of the Gasoline Moke

Gasoline Moke is the competitive product of our company, which follows the century-old classic and is the perfect return of a century-old classic model.

- All chassis and body are aluminum manganese alloy lightweight design.
- Gasoline Moke has been certified by the EEC of the European Union and DOT of the United States
- G-MOKE has high - low automatic switch of the two - speed transmission, so that the car climbing is more powerful, high-speed is more stable.
- G-MOKE uses electronic self - brake system, which is safer and more efficient.
- G-MOKE has Euro 5 certified 600CC two-cylinder engine, which is cleaner, greener and more energy efficient.

2. Product parameter of the Gasoline Moke

Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101

E-mail: zlh7611@hotmail.com

Measurement Parameter	
(L*W*H)	3290*1530*1500 mm
Wheelbase	2120 mm
Wheel track front/rear	1280mm/1280mm
Ground Clearance	180mm
Max climbing ability	23°
Curb Weight	440Kg
Full load	980Kg
Seats	4

3. Product feature and application of the Gasoline Moke

Type	600cc\Water-cooled\8 valves\L2 \ EURO 5 EMISSION
Bore*Stroke (mm)	72*72
Compression Ratio	9.8
Max. Power (kw /rpm)	25/5500
Max. Torque (Nm/rpm)	52/3000--3500
Fuel Supply System	MPFI
Max. Speed km/h	85
Starting	Electric
Min stable speed (rpm)	1000±50

Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101

E-mail: zlh7611@hotmail.com

Min fuel consumption (g/ kw.h)	265
Ignition type	Inductance discharge type
Spark plug modle	LDK7RTC
Distribution type	DOHC
Lubrication type	Pressure spray lubrication
Lubricating oil pump type	Rotor type oil pump
Lubricating oil label	10W-30 SAE
Lubricating oil capacity	1.5-2.2L
Clutch type	Dry-type monolithic clutch
Engine dimension(LXWXH)	404*418*563 mm
Engine weight	61kg
Transmission	Automatic
Drive Train	Front engine, Front drive
Dimension	
L*W*H	3180*1450*1550
Wheelbase	2050mm
Fuel tank Capatity	40L
Ground clearance	200mm
Min turning radius	9 m
Dry Weight	560KG
ChassisSystem	ALUMINUMFRAME

Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101

E-mail: zlh7611@hotmail.com

Braking system (F/R)	Disc Brake (F/R)
Suspension System (F/R)	McPherson independent suspension
Tires/Front/Rear	155/65R13



In the seaside, in the grassland, in the beautiful scenic spots, there are her beautiful figure.



A wonderful car for festive revelry



We are in the same club



Sea and sky, I am the most beautiful guy

Detailed parameters



Shandong Heima Construction Machinery Co. LTD

Tel: +86-13969325101

E-mail: zlh7611@hotmail.com

