

HOLLY-G BEACH

Price (FOB LIANYUNGANG):\$8350.00/unit.

Price adjustment principle: This quotation is based on the exchange rate of RMB to USD 6.6:1. When the exchange rate fluctuation is greater than 5%, the price will be adjusted accordingly.

■ Engine

Type	0.6 cc. Water-cooled. 8 valves. L 2 . EURO 5 EMISSION
Bore*Stroke (mm)	72*72
Compression Ratio	9.8
Max. Power (kw/rpm)	25/5500
Max. Torque (Nm/rpm)	52/3000--3500
Fuel Supply System	MPFI
Max. Speed km/h	100
Starting	Electric
Min stable speed (rpm)	1000±50
Min fuel consumption (g/ kw.h)	265
Ignition type	Inductance discharge type
Spark plug modle	LDK7RTC
Distribution type	DOHC
Lubrication type	Pressure spray lubrication
Lubricating oil pump type	Rotor type oil pump
Lubricating oil label	10W-30 SAE
Lubricating oil capacity	1.5-2.2L
Clutch type	Dry-type monolithic clutch
Engine dimension(LXWXH)	404*418*563 mm
Engine weight	61kg
Transmission	Two-speed transmission, Transmission ratio: 6.7:1 (low speed) 12:1(high speed)
Drive Train	Front engine, Front drive

■ Dimension

L*W*H	3180*1450*1550
Wheelbase	2050mm
Fuel Capacity	40 L
Ground clearance	200mm
Min. turning radius	9 m
Dry Weight	560KG

■ Chassis SystemALUMINUMFRAME

Braking system (F/R)	Disc Brake (F/R)
Packing mode	Electric hand brake.
Suspension System (F/R)	McPherson independent suspension
Tires/Front/Rear	155/65R13
Body color	RED、YELLOW、BLACK、BLUE、WHITE、GREEN



MOQ: 3 units /20 GP.

Loading quantity: 3 units /20 GP, 6 units/40HQ

Leading time: 21 days after 30% deposit down payment.