



Dante PoE 6-Inch Two-Way Active Loudspeaker

SHENZHEN S-TRACK SCIENCE & TECHNOLOGY CO., LTD. is one of China's top three audio system manufacturers and suppliers.S-TRACK® Dante PoE 6-Inch Two-Way Active Loudspeaker (EAGLE DP6) has a built-in DSP processing module and an RJ45 interface. S-TRACK® Dante PoE 6-Inch Two-Way Active Loudspeaker (EAGLE DP6) built-in bass 6.5-inch 1, treble 1-inch imported magnesium film + horn drive.

S-TRACK[®] Dante PoE 6-Inch Two-Way Active Loudspeaker (EAGLE DP6) Product Introduction:

S-TRACK® Dante PoE 6-Inch Two-Way Active Loudspeaker (EAGLE DP6) transmission using Dante transmission for digital, networked transmission management. Dante is based on 3-layer IP network technology, using Dante protocol, simplifying the operation mode of the network, which can realize two-way high-quality large data transmission over long distances, low latency perfect synchronous playback, equipment plug-and-play, system building without topology restrictions, very easy to install and configure, and simple wiring.



S-TRACK® Dante PoE 6-Inch Two-Way Active

Loudspeaker (EAGLE DP6) Product Parameters:

| Unit Configuration | Bass 6.5 inch x 1, Tweeter 1 Inch Imported Magnesium Film + Horn Drive |
|------------------------------|---------------------------------------------------------------------------|
| Sensitivity | 92dB (1w@1m) |
| Output Power | 15.4-30W (Determined by the Output of PoE Powered Devices) |
| Maximum Sound Pressure | 118dB |
| Power | 60W |
| Impedance | 8Ω |
| Vertical Coverage Angle | 60° |
| Horizontal Coverage Angle | 90° |
| Frequency Response Range | 70 Hz-21kHz |
| Connection Jack | RJ45 |
| Transmission Protocol | Dante |
| Power Supply Method | POE Power |
| DSP Processing | Support |
| Installation Method | Self-supporting pendant |
| Net Weight of Loudspeaker | 4.1Kg |
| Speaker Size | 197mm X 300mm X 118mm |

Shenzhen S-Track Science&Technology Co.,Ltd



S-TRACK® Dante PoE 6-Inch Two-Way Active Loudspeaker (EAGLE DP6)Main Features:

1. Built-in amplifier module, digital signal processing.

2. Support for POE power and Dante transmission, single channel, 60W @ 4 ohms.

3. PoE module with Dante™network protocol, 24-bit high-quality audio (44.1K/48KHz)

and control signals can be sent via Dante[™] and controlled via Dante[™]Controller.

★4. This module has an integrated DSP containing gain control, mute control, level,

temperature display, 5-band equalizer control and limit control functions.

All functions can be controlled by Dante-Controller in process on PC or Mac.

S-TRACK® Dante PoE 6-Inch Two-Way Active Loudspeaker (EAGLE DP6) Applications:

S-TRACK® Dante PoE 6-Inch Two-Way Active Loudspeaker (EAGLE DP6) is suitable for use in networked audio systems in conference centers, hotels, stadiums, theaters, multi-function halls, stages, etc.



Shenzhen S-Track Science&Technology Co.,Ltd Tel: +86-13302998794