



## Elevator Air Conditioner

<b>Model name</b>			EA-27
<b>Power supply</b>		<b>V/Hz/Ph</b>	208~230V/60Hz/1Ph
<b>Cooling</b>	<b>Capacity</b>	<b>Btu/h</b>	9500
	<b>EER</b>	<b>W/W</b>	2.5
	<b>Power input</b>	<b>W</b>	1120
	<b>Rated current</b>	<b>A</b>	5.5
<b>Heating</b>	<b>Capacity</b>	<b>W</b>	/
	<b>COP</b>	<b>Btu/w.h</b>	/
	<b>Power input</b>	<b>W</b>	/
	<b>Rated current</b>	<b>A</b>	/
<b>Electric heater (optional)</b>		<b>W</b>	/
<b>Max. input consumption</b>		<b>W</b>	1250
<b>Max. current</b>		<b>A</b>	7
<b>Starting current</b>		<b>A</b>	16
<b>Operation control</b>		-	Remote Control
<b>Indoor coil</b>	<b>Number of row</b>	-	2
	<b>Fin spacing</b>	<b>mm</b>	1.4mm
	<b>Fin material</b>	-	Hydrophilic Aluminum
	<b>Tube outside diameter</b>	<b>mm</b>	φ7
	<b>Tube material</b>	-	φ7×0.24+0.18×C
	<b>Coil widthx height x depth</b>	<b>mm</b>	
	<b>Number of circuit</b>	-	2×2U
<b>Indoor fan motor</b>	<b>Brand</b>	-	Lvzhi
	<b>Model</b>	-	YSK-75-4
	<b>Input</b>	<b>W</b>	95
	<b>Capacitor</b>	<b>uF</b>	5
	<b>Speed(Hi/Lo)</b>	<b>rpm</b>	1250/1100
<b>Indoor air flow (Hi/Lo)</b>		<b>m<sup>3</sup>/h</b>	320/270
<b>Indoor noise level (Hi/Lo)</b>		<b>dB(A)</b>	49/48
<b>Outdoor coil</b>	<b>Number of row</b>	-	2
	<b>Fin spacing</b>	<b>mm</b>	1.4mm
	<b>Fin material</b>	-	Hydrophilic Aluminum
	<b>Tube outside diameter</b>	<b>mm</b>	φ7
	<b>Tube material</b>	-	φ7×0.24+0.18×C
	<b>Coil widthx height x depth</b>	<b>mm</b>	
	<b>Number of circuit</b>	-	2×2U
<b>Compressor</b>	<b>Brand</b>	-	ASN89
	<b>Model</b>	-	GMCC
	<b>Type</b>	-	Rotary
	<b>Capacitor</b>	<b>mF</b>	25
<b>Outdoor fan motor</b>	<b>Brand</b>	-	Lvzhi
	<b>Model</b>	-	YSK-75-4
	<b>Input</b>	<b>W</b>	95
	<b>Capacitor</b>	<b>uF</b>	5
	<b>Speed</b>	<b>rpm</b>	1250/1100
<b>Outdoor noise level (Hi/Lo)</b>		<b>dB(A)</b>	59
<b>Net dimension (W×H×D)</b>		<b>mm</b>	430*580*386
<b>Packing dimension (W×H×D)</b>		<b>mm</b>	485*670*430
<b>Unit weight</b>	<b>Net</b>	<b>kg</b>	30
	<b>Gross</b>	<b>kg</b>	33
<b>Refrigerant</b>	<b>Type</b>	-	R410a
	<b>Charge</b>	<b>g</b>	640
<b>Operation temperature range</b>		<b>°C</b>	17-31
<b>Ambient temperature range</b>		<b>°C</b>	16-48
<b>Loading Qty(20'/40'/40'HQ)</b>		<b>set</b>	192/393/524

Blueway reserves the rights to modify the specifications without notice for product improvement. Please contact us for updated information.