Released

X-band Magnetron Model No. MAF1421B

NSSHNBO

Copyright© Nisshinbo Micro Devices Inc. **Microwave Business Headquarters**

-Notice of Proprietary Information-

This document and its contents are proprietary to Nisshinbo Micro Devices Inc. This publication and its contents may not be reproduced or distributed for any other purpose without the written permission of Nisshinbo Micro Devices Inc.

Those specifications listed in this document are subject to change at any time.

| | Title: | | | |
|----------------------------------|-----------------------|-------|--------|--|
| Nisshinbo Micro Devices Inc. | Datasheet of MAF1421B | | | |
| Microwave Business Headquarters | Reference No.: | Rev.: | Sheet: | |
| Microwave Dusiness rieadquarters | DS-MAF1421B | 04E | 1/3 | |

■ GENERAL DESCRIPTION

MAF1421B is designed for the magnetron of X-band radar system. The frequency range is fixed <9380 - 9440MHz> and the peak output power is 4kW.



■ ELECTRICAL CHARACTERISTICS

| PARAMETERS | | MINIMUM | TYPICAL | MAXIMUM | UNITS |
|--------------------|----------|---------|---------|---------|-------|
| Heater voltage | (note 1) | 5.7 | 6.3 | 6.9 | V |
| Heater current | | 0.5 | 0.55 | 0.6 | А |
| Preheat time | | 60 | - | - | S |
| Peak anode voltage | (note 2) | 3.4 | 3.6 | 3.8 | kV |
| Peak output power | (note 2) | 3.6 | 4.0 | - | kW |
| Frequency | (note 2) | 9380 | 9410 | 9440 | MHz |

ABSOLUTE MAXIMUM RATINGS

These ratings cannot necessarily be used simultaneously and no individual ratings should be exceeded.

| PARAMETERS | | MINIMUM | MAXIMUM | UNITS |
|-------------------------------|----------|---------|---------|-------|
| Peak anode current | (note 3) | 2.0 | 4.0 | А |
| Average anode power input | | - | 13 | W |
| Duty cycle | | - | 0.001 | - |
| Pulse duration | | 0.05 | 1.0 | μs |
| Rate of rise of voltage pulse | | - | 70 | kV/µs |
| Anode temperature | | _ | 100 | °C |
| VSWR at the output coupler | | _ | 1.5 : 1 | _ |

Notes

- 1. With no anode input power. No reduction of heater voltage at operating is required.
- 2. Measured at peak anode current 3.0A.
- 3. Any overshoot of the anode current is not acceptable. And, sagging waveform of the anode current causes the poor spectrum and the shifting frequency in the pulse since a magnetron current pushing characteristics.


* Above Specifications are subject to change without notice.



Nisshinbo Micro Devices Inc.

| Reference No.: | Rev.: | Sheet: |
|----------------|-------|--------|
| DS-MAF1421B | 04E | 2 |

OUTLINE




Anode temperature measured at this point

| D | EMENSIONS | S U | nit:mm |
|---|------------------------|-----|----------------------|
| Α | 60±0.2 | Κ | $2-\phi 4.4 \pm 0.1$ |
| В | 3.75 | L | 9 |
| С | 32.5 ± 0.1 | М | 7 |
| D | 31±0.1 | Ν | 3 3 M A X |
| Е | 41.3 | Ρ | 43 |
| F | 72 | R | 17 |
| G | 70 | S | 3 |
| Η | 20 | Т | 185±10 |
| J | $4-\phi 4.32 \pm 0.08$ | | |

| Lead Connection | Lεa | a d | Сo | n n | е | c t | i | ons |
|-----------------|-----|-----|----|-----|---|-----|---|-----|
|-----------------|-----|-----|----|-----|---|-----|---|-----|

| Colour | Element |
|--------|-----------------|
| Green | Heater |
| Yellow | Heater, Cathode |



Top view

(Dimensions are expressed in "mm".)

* Above Specifications are subject to change without notice.



Nisshinbo Micro Devices Inc.

| Reference No.: | Rev.: | Sheet: |
|----------------|-------|--------|
| DS-MAF1421B | 04E | 3 |