



Compact ICS

Integrated Communication System

- $\begin{tabular}{ll} \hline \end{tabular} \begin{tabular}{ll} \hline \end{$
- ✓ IP-22 Rating
- Capacity: Up to 72 lines
- Oual power supply: AC/DC or AC/AC



SIP



Onboard communication

Description

The flexible configuration of the Compact ICS provides a cost effective solution for intercom, telephone, Public Address and loudhailing. The modern architecture offers network connection including cascading, remote service and interface to/from other IP based systems and components. The Compact ICS system is compatible with all existing intercom stations and offers a unique combination of analog, digital and IP based communication terminals. By adding the ICS P-6202 Billing Unit, logging and billing of calls are trackable using PIN and extension registration.

page 1/2

Specifications

MECHANICAL

Dimensions (WxHxD)	618x585x470 mm	
Weight	30 kg	
PRODUCT VARIANTS		
THOUSE TAINAITE		
4000019779	Compact ICS 24 lines, AC/DC	
4000019780	Compact ICS 24 lines, AC/AC	
4000019781	Compact ICS 48 lines, AC/DC	
4000019782	Compact ICS 48 lines, AC/AC	
4000019823	Compact ICS 72 lines, AC/DC	
4000019824	Compact ICS 72 lines, AC/AC	

page 2/2