

ADJUSTABLE TABLE COMPASS 卓上修正式



TABLE COMPASS (Type Approval)



Certificate No.	Model	Card Dia. (inch)	H (mm)	W (mm)	Weight (kg)
#1958	T-130SLK	5"	328	420	6.8
#1959	T-150SLK	6"	355	460	10.2

標準付属品付 (Each unit is provided with standard accessories)

下部照明式 (Bottom-lighting, DC 24V)

非常用電源切換スイッチ付 (Wigh switch for emergency power)

Adaptation temperature between -20c and 60c.

4 インチコンパスは船舶検査(カード径115mm以上)の規格に沿わないため製造を終了しております。



TABLE COMPASS (Non Type Approval)



Model	Card Dia. (inch)	H (mm)	W (mm)	Weight (kg)
T-130SL	5"	328	420	6.8
T-150SL	6"	355	460	10.2
T-165SL	6.5"	383	490	11
T-180SL	7"	383	490	11

標準付属品付 (Each unit is provided with standard accessories)

下部照明式 (Bottom-lighting, DC 24V)

Adaptation temperature between -20c and 60c.



KITAKO社製のセンサーが取り付けられているコンパスを取り換えの場合、トップガラスの取り換えが必要です。

TABLE COMPASS (輸出向け)



Model	Card Dia. (inch)	H (mm)	W (mm)	Weight (kg)
T-100B	4"	300	389	5.1
T-130B	5"	305	420	5.6
T-150B	6"	320	457	6.8
T-180B	7"	332	492	9.4

標準付属品付(Each unit is provided with standard accessories)

上部照明式(Upper-lighting,DC 24V)

