

IBUKI EBW-300 Electronic bell series is compact lightbody built in electronic pronunciation system. Clear bell tone is generated from a voice synthesis circuit. Compared with mechanical bell needed the adjustment during installation, IBUKI electronic bell operates always stably just on voltage. Ultra bright LED is installed as visible waring indication which does not exist burn-out bulb trouble on light bulb type. Internal DIP switch changeovers the continuous / interrupt operation of sound and light. CE Mark has been acquired.

- Sound level : 102dB/1m
- Volume adjustable
- Lightweight, low power consumption
- Clear bell tone on electronic voice synthesis
- Ultra bright LED indication
- Easy setting
- Changeover the tone continuous / interrupt
- Changeover the light continuous / flicker
- CE Mark acquired



EB-300S Wall Mount



EB-300F Flush Mount



EBW-300 Waterproof Wallmount

	DIP SWITCH	REMARK
SOUND	ON <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 BELL CONTINUOUS SOUND	
	ON <input type="checkbox"/> 1 <input checked="" type="checkbox"/> 2 BELL INTERRUPTED SOUND	
LIGHT	ON <input type="checkbox"/> 1 <input checked="" type="checkbox"/> 2 LAMP CONTINUOUS	
	ON <input type="checkbox"/> 1 <input type="checkbox"/> 2 LAMP FLICKER	

Type	Protection	Sound Level (dB/1m)	Voltage	Size WXLXH (mm)	Weight (kg)
EB300S	IP22	102dB (A)	AC100V 0.1A	91X130X84	0.5
EB300F			AC220V 0.05A	121X150X84	0.6
EBW300	IP56		DC24V 0.4A	91X154X84	0.5

