

IBUKI Electronic alarm is a compact unit consists of speaker and oscillator, the sound dB is 110dB to 115dB. 8 tones are preset, EA110, EA113S and EA115 electronic alarm are produced 1 tone by the selection of inner switch. EA110E and EA115E are changeover 8 tones operated by external control. Variant models are available on sound level, waterproof and combined unit with lamp, rotate light and strobo light.



EA110



EA113S

NO.	Tone
1	QUU QUU (Repeated)
2	PIPO PIPO (Repeated)
3	AS SIREN (Repeated)
4	AS SIREN (Continuous)
5	PI — (Continuous)
6	PO — (Continuous)
7	PI PI (Repeated)
8	PO PO (Repeated)



EA115

Type	Protection	Tone	Sound Level (dB/1m)	Voltage	Length (mm)	Horn Diameter (mm)	Weight (kg)			
EA115	IP56	1 Tone Select	115dB	AC220V 0.1A	308	310	5			
EA115E		8 Tone		AC100V 0.2A						
EA113S		1 Tone Select	113dB	DC24V 0.6A				260	152	2.5
EA110		1 Tone Select	110dB	AC220V 0.1A				276	152	5
EA110E	8 Tone	AC100V 0.2A								
				DC24V 0.6A						

■ IBUKI Alarm Combination (Example)



Model

Lamp with Lamp

RF4 with RF4 rotating light